10/565760

IAP6 Rec'd PCT/PTO 24 JAN 2006 Sheet 1 of 1

Form PTO-1449 (REV. 1/06)		US Dept. of Commerce PATENT & TRADEMARK OFFICE		ATTY DOCKET NO. 126790			APPLICATION NO. National Stage Patent Application of			
INFORMATION DISCLOSURE STATEMENT					•		PCT/JP200	04/007619		
(Use several sheets if necessary)					APPLICANT Makoto IIDA					
					FILING DATE January 24, 2006					
	,	U.	S. PATEN	r DOCUN	MENTS			_		
Examiner Initials	Cite No.	Document Number	Date		Name ,					
								•		
					^					
		FORE	EIGN PATE	NT DOC	UMENTS					
Examiner Initials	Cite No.	Document Number	Da	te	Country		With English Abstract	With English Translation		
FH.	1	WO 02/00970 A1	01/03/20	02	WIPO		х	_		
FH.	2	JP 2002-137987 A	05/14/20	02	JAPAN		x	х		
Filt.	3	JP 2004-338979 A	12/02/20	04	JAPAN ·		х	х		
					,					
			OTHER D	OCUME	NTS					
Examiner Initials	Cite No.	(Including Author, Title, Date, Pertinent Pages, etc.)								
FH.	4	V.V. VORONKOV, "The Mechanism of Swirl Defects Formation in Silicon," Journal of Crystal Growth, 59 (1982), pp. 625-643								
				-						
····										
		-								
		1								
EXAMINER		telis filesto				DATE CO	NSIDERED A	7		
Examiner:		itation considered, whether or not citation				ough citat	ion if not in	conformance		

Date: January 24, 2006

10/565760

IAP6 Rec'd PCT/PTO 24 JAN 2006 Sheet 1 of 1

Form PTO-1449 (REV. 1/06)		US Dept. of Commerce PATENT & TRADEMARK OFFICE ATION DISCLOSURE STATEMENT		ATTY DOCKET NO. , 126790			APPLICATION NO. National Stage Patent Application of PCT/JP2004/007619					
(Use several sheets if necessary)				APPLICANT Makoto IIDA								
					DATE 24, 2006		Ţ					
U.S. PATENT DOCUMENTS												
Examiner Initials	Cite No.	Document Number	Date		Name							
ļ												
	· .											
		FORE	IGN PATE	NT DOC	UMENTS			г				
Examiner Initials	Cite No.	Document Number	· Da	te	Country		With English Abstract	With English Translation				
F.H.	1	WO 02/00970 A1	01/03/20	02	WIPO		х					
F.H.	2	JP 2002-137987 A	05/14/20	02	JAPAN		x	х				
БH.	3	JP 2004-338979 A	12/02/2004		JAPAN		x	х				
			OTHER D	ОСИМЕ	NTS							
Examiner Initials	Cite No.	(Including Author, Title, Date, Pertinent Pages, etc.)										
F.H.	4	V.V. VORONKOV, "The Mechanism of Swirl Defects Formation in Silicon," Journal of Crystal Growth, 59 (1982), pp. 625-643										
	, -											
		1										
EXAMINER	9	elisit telepe Date considered 6/5/2009										
Examiner:	Initial if citation considered, whether or not citation is in conformance with M.P.E.P. 609; draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant.											

Date: January 24, 2006

*B Reference

(12)特許協力条約に基づいて公開された国際出題

(19) 世界知的所有権機關 国際事務局



(43) 国際公開日 2002年1月3日 (03.01.2002)

PCT

(10) 国際公開番号 WO 02/00970 A1

(51) 国際特許分類?:

C30B 29/06, 15/04

(21) 国際出窟番号:

PCT/JP01/05361

(22) 国際出願日:

2001年6月22日(22.06.2001)

(25) 国際出窟の言語:

日本語

(26) 国際公開の官語:

日本語

(30) 優先権データ:

特願2000-192317 2000年6月27日(27.06.2000) JP

(71) 出願人 (米国を除く全ての指定国について): 信越半 導体株式会社 (SHIN-ETSU HANDOTAI CO., LTD.) [JP/JP]; 〒100-0005 東京都千代田区丸の内1丁目4番2 号 Tokyo (JP).

(72) 発明者; および

(75) 発明者/出願人 (米国についてのみ): 飯田 〒 〒 (IIDA)

Makoto) [JP/JP]; 〒379-0196 群馬県安中市磯部2丁目 13番1号 倡越半導体株式会社 半導体機部研究所内 Gumma (JP). 山田好彦 (YAMADA, Yoshibiko) [JP/JP]; 〒379-0196 群馬県安中市磯部2丁目13番1号 信越半 導体株式会社 礎部工場内 Gunma (JP).

(74) 代理人: 好宮幹夫(YOSHIMIYA, Mikio); 〒111-0041 東京都台東区元浅草2丁目6番4号 上野三生ピル4F Tokyo (JP).

(81) 指定国 (国内): JP, KR, US.

(84) 指定国 (広域): ヨーロッパ特許 (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).


添付公開書類:

国際調査報告書

2文字コード及び他の略語については、定期発行される 各PCTガゼットの巻頭に掲載されている「コードと略語 のガイダンスノート」を参照。

(54) Title: METHOD FOR PRODUCING SILICON SINGLE CRYSTAL

(54) 発明の名称: シリコン単結晶の製造方法



(57) Abstract: A method for producing a silicon single crystal by the CZ method, characterized in that an inner diameter (c) of a crucible (32) having a silicon raw material therein is 2 to 2.5 times an intended diameter (d) of the silicon single crystal (1) to be produced, and the silicon single crystal is pulled up in a manner wherein the minimum value of a ratio (V/Gs) in the direction of diameter of a velocity (V) of pulling up to a temperature gradient (Gs) in the interface between solid and liquid in the crystal is 0.3 mm²/K? min or more. The method allows the decrease of the temperature gradient (G1) in a melt, the increase of the maximum velocity of pulling up, and the suppression of occurrence of an OSF ring, by the use of the ordinary CZ method, with ease and simplicity, and at a low cost.